

Pinstamp Marking Systems

TMM 4250 Telesis Integrabile Multiple Pin



TMM 4250 Multiple Pin Marking Systems.



La testa di marcatura del TMM4250 ha un'area di marcatura di 13mm x 50mm e 4 punte. Può marcare fino ad 8 caratteri al secondo. L'elevata protezione IP55 permette l'installazione e la durata nel tempo anche in ambienti contaminati da solidi o liquidi. Può essere integrata facilmente grazie alle sue dimensioni contenute.

TMM 4250 Specifications

- NEMA 12-Rated (IP55) with rubber boot for protection against solid and liquid Contaminants
- Extremely compact for ease of integration
- Available with four 25S or two 150SA marking pins
- Marks up to eight 0.125" (3mm) high characters-per-second
- Self-contained, state-of-the-art TMC470 controller features two serial ports, USB and Ethernet ports
- Stores up to 200 marking patterns
- Marking windows up to 0.5" x 2" (13mm x 50mm)
- Depths up to 0.013" (0.33 mm) in mild steel
- Rugged rack-and-pinion X/Y platform for low maintenance operation
- Detachable electronics cable for improved serviceability
- RS232 or TCP/IP Host interface to download text to individual fields or call up entire patterns
- Automatically generates serial numbers, date, time and shift codes
- Easily interfaced to PLCs (Programmable Logic Controllers) and Host Computers

